


FASTENING METHODS

Thielco has a range of fastenings for each type of grating and to suit all lower support construction. The fastening material consists of steel according to S235 JR and is galvanized according to NEN and ISO 1461. Fixing options are also available in RVS 304 stainless steel.

Range

Grating clamp for type R and SP hot dip galvanized

- upper clip available for mesh 22.8, 34.3, 45.7, 57.1, 68.6 centre-to-centre bearing bars
- lower clamp with a 65 mm slot
- back bolt M8 x 50 mm, M8 x 70 mm, M8 x 90 mm or M8 x 90 mm
- nut M8




Grating clamp for type A hot dip galvanized

- single upper clip
- lower clamp with a 65 mm slot
- back bolt M8 x 50 mm, M8 x 70 mm or M8 x 90 mm
- nut M8




Safety clamp for type SP for mesh 34 x 38 mm

- special safety upper clip
- lower clamp with a 65 mm slot
- bolt M8 x 50 mm, M8 x 70 mm or M8 x 90 mm
- nut M8



Coupling clamps to join adjacent grating sections

- 2 upper clips, 2 bolts M8 x 50 mm, 70 mm or 90 mm
- 2 nuts M8
- lower clamp (U profile) with 2 65 mm slots



THIELCO STAALINDUSTRIE B.V.

Dr. Poelsstraat 2, 5953 NP Reuver, The Netherlands PO Box 4788, 5953 ZK Reuver, The Netherlands
T +31 (0)77 47 69 350 F +31 (0)77 47 69 330 E info@thielco.nl I www.thielco.nl

Bank: ABN AMRO BANK NV Venlo Bankrek. nr.: 48.40.83.465 Bic (swift): ABNANL2A IBAN: NL84 ABNA 0484083465 ING Bankrek. nr.: 1057859
VAT NL803220960B01 chamber of commerce Venlo nr.: 12018079

All our quotations, all orders placed with us and all contracts concluded with us are subject to the METAALUNIECONDITIONS, filed with the registrar of the District Court of Rotterdam, as enclosed. The conditions of delivery and payment will also be sent to you upon request.

GEOMET, GRATINGS, STAIRTREADS, HOTDIP GALVANIZING, POWDERCOATING, HOTDIP CENTRIFUGAL GALVANIZING, MECHANICAL PLATING